



ZEP Manufacturing Company
 Acuity Specialty Products Group, Inc.
 P.O. Box 2015
 Atlanta, GA 30301
 1-877-I-BUY-ZEP (428-9937)
 www.zep.com

Material Safety Data Sheet and Safe Handling and Disposal Information

Section 1. Chemical Product and Company Identification

Product name ZEP-PAR NC
Product Use Aerosol Silicone Lubricant
Product Code 0107
Date of issue 12/28/04 **Supersedes** 02/13/04

Emergency Telephone Numbers For MSDS Information:
 Acuity Specialty Products Group, Inc.
Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency
 INFOTRAC:
(877) 541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency
 CHEMTREC:
(800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Printing date: 12/29/04

Prepared by Compliance Services Group
 Acuity Specialty Products Group
 1420 Seaboard Industrial Blvd.
 Atlanta, GA 30318

Section 2. Composition, Information on Ingredients

Name of Hazardous Ingredients	CAS #	% by Weight	Exposure Limits
HEPTANE; n-heptane	142-82-5	60 - 70	ACGIH/OSHA (United States). TWA: 400 ppm 8 hour(s).
BLEND OF ISOBUTANE & PROPANE	74-98-6; 75-28-5	20 - 30	ACGIH/OSHA (United States). STEL: 400 ppm 15 minute(s). ACGIH TLV (United States). TWA: 800 ppm 8 hour(s). OSHA PEL (United States). TWA: 1000 ppm 8 hour(s).

Section 3. Hazards Identification

Acute Effects

Routes of Entry Dermal contact. Inhalation.

Skin Hazardous in case of skin contact (irritant, permeator). Skin inflammation is characterized by itching, scaling, or reddening. Product may be dermal absorbed. Defatting properties, may aggravate an existing dermatitis.

Eyes Hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching.

Inhalation Hazardous in case of inhalation (lung irritant). Avoid breathing vapors or spray mists. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system depression. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Ingestion Harmful if swallowed. Aspiration hazard if swallowed- can enter lungs and cause damage. Vomiting increases risk of chemical pneumonia.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse health effects are lessened by following all prescribed safety precautions, including use of proper personal protective equipment.

Carcinogenic Effects

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Chronic Effects

Over-exposure by inhalation or absorption can cause central nervous system depression. Prolonged skin contact may cause dermatitis with drying and cracking of skin.

See Toxicological Information (section 11)

HMIS

Health	1
Fire Hazard	4
Reactivity	0
Personal Protection	B,X

Section 4. First Aid Measures

Eye Contact

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion Aspiration hazard if swallowed- can enter lungs and cause damage. Do NOT induce vomiting unless directed to do so by medical personnel. If vomiting occurs, keep head lower than hips to help prevent aspiration. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point Closed cup: <-18°C (<0°F) (Tagliabue.) **Flammable Limits** LOWER: 1.2% UPPER: 6.7%

Flammability Extremely flammable. (CSMA) Aerosol that may flashback.

Fire Hazard FLAMMABLE LIQUID AND VAPOR. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions or when heated.

Fire-Fighting Procedures Dry chemical, carbon dioxide, foam. Wear special protective clothing and positive pressure, self-contained breathing apparatus. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.



Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Extremely flammable liquid and vapor. Store and use away from heat, sparks, open flame, or any other ignition source. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or spray mists. Use only with adequate ventilation. Wash thoroughly after handling. Wash contaminated clothing before reusing.

Storage CONTENTS UNDER PRESSURE. Store and use away from heat, sparks, open flame, or any other ignition source. Keep away from heat and direct sunlight. Keep container in a cool, well-ventilated area. Do not store above 49°C (120.2°F). Do not puncture or incinerate. Keep out of the reach of children.

Section 8. Exposure Controls, Personal Protection

Personal Protection

Protective Clothing (Pictograms)

Eyes Safety glasses with side shields.

Body Chemical resistant gloves. (Viton, Nitrile, Neoprene)

Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Wear appropriate respirator when ventilation is inadequate. Approved/certified respirator with organic vapor cartridges.



Section 9. Physical and Chemical Properties

Physical State Liquid. (Aerosol.) **Color** Colorless.

pH Not applicable. **Odor** Solvent-like.

Boiling Point Not determined. **Vapor Pressure** Not determined.

Specific Gravity 0.69 (Water = 1) **Vapor Density** Not determined.

Solubility Insoluble in cold water, hot water. **Evaporation Rate** Not determined.

VOC (Consumer) 91.4% 5.22 (lb/gal) 626 (g/l)

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products Carbon Dioxide, Carbon Monoxide and other organic materials..

Section 11. Toxicological Information

Toxicity to Animals Not available.

Section 12. Ecological Information

Ecotoxicity Not available.

Biodegradable/OECD Not available.

Section 13. Disposal Considerations

Waste Information Waste must be disposed of in accordance with federal, state and local environmental control regulations. **Waste Stream** Code: D001
Classification: - (Hazardous waste.)
Origin: - (RCRA waste.)

Consult your local or regional authorities.

Section 14. Transport Information**Proper shipping name** Consumer Commodity**DOT Classification** ORM-D**UN number** Not regulated.

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

Section 15. Regulatory Information**U.S. Federal Regulations** SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean air act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA inventory.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.